



## TECHNICAL DATA

### Power

Lithium-iron battery	51.2 V/20.48 kWh
Voltage	48/24 V
Emissions	None

### Performance

Traction - DC electric motor	2x3 kW
Standard rubber tracks	180x72x40
Continuous travel speed - forward	2.8 mph
Continuous travel speed - reverse	2.5 mph
Ground pressure	4.82 psi

### Operating force

Traction force	14 kN/ 3147 lbs
Breakout force	8 kN/ 1798 lbs
Lifting force	11 kN/ 2473 lbs

### Loader Attachment System

Hydraulic Pump Drive - DC electric motor	1x 4.5 kW
Auxiliary Hydraulic Pump Flow	5.3 gpm
Auxiliary Hydraulic Pump Pressure	2,175 psi
Attachment Pin Activation	Electronic
Hydraulic system pressure release	Electronic
Loader Arms	Radial
Loader arm float function	Yes
Hydraulic oil tank capacity	7.92 gallons

### Electric system information

Telematics (GSM/GPS/speedometer, inclinometer)	Yes
Radio controller	160 ft
Integrated single-phase charger with Universal input voltage	90/265 VAC

### Lighting

LED working light	60W
Working beacon	Orange / Green

### Dimensions

Front turning radius	64.56 inch
Contour turning radius rear	42.52 inch
Width with bucket	33.86 inch
Hinge pin Height	86.65 inch
Ground clearance	4.13 inch

### Weights

Operating weight of the machine	2381 lbs
Total weight of the machine	3381 lbs
Rated Operating Capacity (ROC)	1000 lbs

